

## PRODUCT SPECIFICATION



TO MARKET

Composition	Recycled Vinyl
Installation	Glue Down; Perimeter Glue
Size	7.08" x 47.24" / 12" x 24"
Gauge	5.0mm
Wear Layer	20 mil
Edge	Square
Finish	Ozocoat+ Technology Advanced Ceramic Bead Barrier + Coating, Antifungal, Antibacterial, No Wax, No Buff
Certifications	FloorScore®; Environmental Product Declaration (EPD); ISO-9001 / ISO-14001
Warranty	Lifetime Residential / 15-Year Commercial
Reference Specifications	ASTM F-1700 Solid Vinyl Floor Tile – Class III, Type B-Embossed Meets & Exceeds Passing Requirements for composition, size, thickness, squareness, flexibility, dimensional stability and resistance to chemicals.
Radiant Panel	ASTM E-648 Critical Radiant Flux – Class I Meets & Exceeds Passing Requirements
Static Load Limit	ASTM-F-970 Meets & Exceeds Passing Requirements
Slip Resistance	ASTM D-2047 (James Machine) >.6 Meets & Exceeds Passing Requirements
Packaging	7.08" x 47.24" - 2.32 sq.ft./tile; 23.25 sq.ft./carton; 1,046 sq.ft./pallet; 45 cartons/pallet; 20 pallets/container  12" x 24" - 2 sq.ft./tile; 20 sq.ft./carton; 960 sq.ft./pallet; 48 cartons/pallet; 20 pallets/container
Country of Manufacture	Korea

For additional information + product samples, please contact To Market Global.