

PRODUCT SPECIFICATION



TO MARKET

Composition	Virgin Vinyl – Phthalate Free
Installation	Glue down
Size	7.08" x 47.24"
Gauge	2.0mm (0.080")
Wear Layer	12 mil
Finish	Advanced Ceramic Bead Barrier + Coating No Wax, No Buff
Certifications	FloorScore®; Environmental Product Declaration (EPD); ISO-9001 / ISO-14001
Warranty	15-Year Residential / 8-Year Commercial
Reference Specifications	ASTM F-1700 Solid Vinyl Floor Tile – Class III, Type B-Embossed Meets & Exceeds Passing Requirements for composition, size, thickness, squareness, flexibility, dimensional stability and resistance to chemicals.
Radiant Panel	ASTM E-648 Critical Radiant Flux – Class I Meets & Exceeds Passing Requirements
Static Load Limit	ASTM-F-970 Meets & Exceeds Passing Requirements
Slip Resistance	ASTM D-2047 (James Machine) >.6 Meets & Exceeds Passing Requirements
Packaging	2.32 sq.ft./plank; 41.85 sq.ft./carton; 2,513 sq.ft./pallet; 60 cartons/pallet; 20 pallets/container
Country of Manufacture	United States of America

For additional information + product samples, please contact To Market Global.