

TO MARKET RT200 ACOUSTIC UNDERLAYMENT



Information + Specifications

RT200 Impact Sound Underlayment is a high performance acoustic underlayment designed to reduce the passage of impact transmission caused by people walking. It can be installed under sheet vinyl, LVT, ceramic tile and stone, carpet, carpet tile and hardwood flooring.

RT200 underlayment has been specifically engineered and manufactured for use with OzoTec, OzoGrip, Urban 20, Urban 12, Urban 8 + Urban 6.

RT200 is manufactured from 100% recycled high-density foam chips and cork granules. It is the perfect solution to reduce vibration caused by footfalls and impact noise.

SPECIFICATIONS

Thickness:	2mm or 1/8"
Roll Size:	4' x 50' – 200 square feet per roll
Weight:	0.35 lbs. per square foot
Density:	ASTM D-792 – 43 lbs. per cubic foot
Hardness:	A Shore Durometer 40-55
Environmental Rating:	Green Circle Certified

Acoustical	Concrete Slab – 152mm
Performance:	STC – 52, IIC – 51, Delta IIC – 23
	Ceiling Assembly – 3023x3632mm
	STC – 50, IIC – 50, Delta IIC – 21

APPLICATIONS

Apartments
Condominiums
College dormitories

Class rooms
Schools
Hospitals

Any other areas
where reduction of
impact noise is desired