

PRODUCT SPECIFICATIONS

Size:	Straight Edge Tile: 38"x38" – 10.02 s/f per tile Interlocking Tile: 37"x37" – 9.50 s/f per tile	
Thickness:	Standard backing 6mm (1/4"), 8mm (5/16") and 10mm (3/8") High Density 8mm HD+ (heavy weight training)	
Composition:	Dual layer tile with homogeneous solid color top layer, composed with a two-part high pressure proprietary applied protective Shield+ coating. Backing layer non-vulcanized post-consumer recycled SBR (styrene butadiene rubber) or pre and post-consumer recycled regrind bound with a proprietary slow-cured MDI water based polymer.	
Finish:	Matte	
Floorscore®:	Certified SCS-FS-02937	
ASTM D2047	Static Coefficient of Friction (James Machine method) Dry.96/ Wet 0.84	
ASTM D3676	Density Foam Test Summary 53.8 lbs. /cu. ft.	
ASTM D395B	Compression Set Under Force	2.4% recovered
ASTM E492	Tensile Strength302.5 lb./sq. in.	
ASTM-E648	Critical Radiant Flux passes (complete details available upon request through your To Market sales representative)	
ASTM F137	Flexibility	6mm Mandrel Passes
ASTM F970-87	Static Load	.001 inch
ASTM G21	Mold Growth on Surface	no mildew after 28 days
CA 01350	VOC Emissions Section 01350 Passes	
Warranty	10-year limited commercial warranty	
Manufactured	Canada	